

EA900Pro

10 kVA ~ 15 kVA (3:3)
PF 1.0



Features

- DSP digital control technology
- Active power factor correction (APFC), input power factor up to 0.99
- Output power factor 1.0
- Cold start
- Dual input
- Wide input voltage range (121 V ~ 277 V)
- Auto sensing frequency
- 50 / 60 Hz frequency conversion mode
- Work efficiency up to 97% in ECO mode
- Auto control fan speed when loads varies
- Auto power ON/OFF according to the load capacity set by users
- Flexible battery configuration for using 14 / 16 / 18 / 20 pcs batteries
- Compact internal layout miniaturizes the complete unit for small footprint
- 5" colorful touch screen display, friendly human-machine interface
- Powerful background software for parameters configuration and online updating
- Doubling the battery charging speed, 90% capacity restored in 4 hours (standard model UPS)
- Linear derating in low voltage input reducing battery discharging times
- Advanced battery management (ABM), automatic floating / equalizing charge control, charger dormancy control
- Configurable switching time from battery mode to mains mode when mains power is restored
- Effective software and hardware protection function, powerful self-diagnostic function, abundant historical records
- Standard emergency power off (EPO)
- Standard maintenance bypass
- Standard RS232 / USB communication port
- Optional RS485 / SNMP / AS400 communication port and SMS alarms
- Optional N+X redundancy parallel up to 6 units
- Optional battery temperature compensation, EMD environmental sensors

Rear Panel

1. Mains Input
2. DC Input
3. Bypass Input
4. Output
5. Mains Input Breaker
6. Bypass Input Breaker
7. Maintenance Bypass
8. Fan
9. RS232
10. USB
11. EPO
12. Battery Temperature Compensation (Optional)
13. Intelligent Slot 1 (SNMP / AS400 / RS485 Optional)
14. Intelligent Slot 2 (SNMP / AS400 / RS485 Optional)
15. Parallel Card (optional)
16. Battery Breaker
17. Battery Cold Start



Optional 5" color touchscreen display



10 ~15KVA long time model

10 ~ 15KVA standard model

Specifications

| MODEL | EA9010P | EA9015P |
|------------------------------------|---|--------------------------------|
| Capacity | 10 KVA / 10 KW | 15 KVA / 15 KW |
| INPUT | | |
| Rated voltage | 173 Vac / 190 Vac / 200 Vac / 208Vac / 220 Vac | |
| Voltage range | 156 ~ 277 Vac (no derating); 121 ~ 156 Vac (linear derating between 60% and 100% load) | |
| Rated frequency | 50 / 60 Hz (auto-sense) | |
| Frequency range | 40 ~ 70 Hz | |
| Power factor | ≥ 0.99 | |
| Total harmonic distortion (THDi) | ≤ 5% | |
| Bypass voltage range | -40% ~ +15% (settable) | |
| OUTPUT | | |
| Voltage | 173 Vac / 190 Vac / 200 Vac / 208Vac / 220 Vac (settable) | |
| Voltage regulation | ± 1% | |
| Frequency | 45 ~ 55 Hz or 55 ~ 65 Hz (synchronized range); 50 / 60 Hz ± 0.1 Hz (battery mode) | |
| Waveform | Sinusoidal | |
| Crest factor | 3:1 | |
| Total harmonic distortion (THDu) | ≤ 2% (linear load); ≤ 5% (non-linear load) | |
| Transfer time | Mains mode to battery mode: 0 ms; Inverter mode to bypass mode: 0 ms | |
| Inverter overload capability | 102% ~ 125%: transfer to bypass in 10 mins; 125% ~ 150%: transfer to bypass in 1 min; > 150%: transfer to bypass in 0.5 s | |
| Bypass overload capability | 102% ~ 125%: shut down in 20 mins; 125% ~ 150%: shut down in 2 mins; > 150%: shut down in 1 s | |
| BATTERIES | | |
| DC voltage | Standard model: 240 VDC; Long time model: 192 VDC (168 V / 192 V / 216 V / 240 VDC optional) | |
| Inbuilt battery of standard model | 20 × 9 Ah (40 / 60 × 9 Ah optional) | 40 × 9 Ah (60 × 9 Ah optional) |
| Recharge time | Standard model: 90% capacity restored in 4 hours; Long time model: depend on the capacity of battery | |
| SYSTEM | | |
| Efficiency | ≥ 90%, ECO mode 97% | |
| Display | 5" colorful touch screen | |
| Alarm | Battery mode, low battery, fans fault etc. | |
| Max. parallel numbers | 6 | |
| EMI | IEC/EN62040-2 | |
| EMS | IEC61000-4-2 (ESD) | |
| | IEC61000-4-3 (RS) | |
| | IEC61000-4-4 (EFT) | |
| | IEC61000-4-5 (surge) | |
| COMMUNICATIONS | | |
| RS232 / USB / RS485 / dry contacts | Supports Windows® 98/2000/2003/XP/Vista/2008/ Windows® 7/8/10 | |
| SNMP | Power management from SNMP manager and web browser | |
| OTHERS | | |
| Humidity | 20~90% RH @ 0~40°C (non-condensing) | |
| Noise level | ≤ 65dB (1m) | |
| Dimensions (W×D×H)(mm) | 350 × 655 × 732 (H) | |
| | 350 × 785 × 1078 (S) | |
| Packaged dimensions(W×D×H)(mm) | 472 × 780 × 920 (H) | |
| | 472 × 910 × 1260 (S) | |
| Net weight (kg) | 61 (H), 125 (S) | 65 (H), 175 (S) |
| Gross weight (kg) | 71 (H), 140 (S) | 75 (H), 200 (S) |

- Derate capacity to 90% when the output voltage is adjusted to 173 Vac.
- S means standard model, H means long time model.

- All specifications subject to change without notice.
- Custom-made specifications are acceptable.