

EA5KTSI / EA6KTSI / EA8KTSI / EA10KTSI / EA13KTSI / EA16KTSI (Three-Phase)

- Compact and contemporary design
- Unmatched power density
- Highest efficiency in the industry (max. 98.65%)
- Fuseless and fanless design
- Industrial-grade high quality components
- All-round lightning protection
- IP65 waterproof and dustproof
- Smart connected



Technical Data

MODEL	EA5KTSI	EA6KTSI	EA8KTSI	EA10KTSI	EA13KTSI	EA16KTSI
INPUT (DC)						
Max. input power	6.5 kW	7.8 kW	10.4 kW	13 kW	16.9 kW	20.8 kW
Max. input voltage			1000 V			
Start-up voltage			180 V		250 V	
MPPT voltage range		120 - 950 V			200 - 950 V	
MPPT voltage range at full load	185 - 850 V	220 - 850 V	290 - 850 V	370 - 850 V	410 - 850 V	500 - 850 V
Max. input current		14A / 14A			11 A × 2 / 11 A	
Max. short circuit current		15 A / 15 A			12 A × 2 / 12 A	
Number of MPPTs			2			
Number of DC inputs		A:1 / B:1			A:2 / B:1	
OUTPUT (AC)						
Rated output power	5 kW	6 kW	8 kW	10 kW	13 kW	16 kW
Max. active power	5 kW	6 kW	8 kW	10 kW	13 kW	16 kW
Max. apparent power	5 kVA	6 kVA	8 kVA	10 kVA	13 kVA	16 kVA
Max. output current	7.3 A	8.7 A	11.6 A	14.5 A	18.9 A	23.2 A
Rated grid voltage		230 / 400 V, 3 W + N + PE				
Grid voltage range		176 - 276 V / 304 - 480 V				
Rated grid frequency			50 / 60 Hz			
Grid frequency range			45 - 55 Hz / 55 - 65 Hz			
THD			< 3% (rated power)			
Output current DC component			< 0.5% I _n			
Power factor			> 0.99 (rated power)			
Power factor adjustable			0.8 leading ~ 0.8 lagging			
EFFICIENCY						
Max. efficiency		98.65%				
European efficiency		98.2%				
OTHERS						
Protections	Anti-islanding protection, output overcurrent/overvoltage protection, leakage current protection, DC reverse polarity protection, DC/AC surge protection, ground insulation resistance detection, DC switch (standard), PID prevention and restoration (optional)					
Communications	RS485, Wi-Fi/Ethernet (optional), GPRS (optional)					
Display	LED, Bluetooth (optional)					
Self-consumption at night	< 1 W					
IP rating	IP 65					
Cooling	Natural cooling					
Isolation	Transformerless					
Standards	IEC/EN 62109-1, IEC/EN 62109-2, VDE AR-N-4105, AS/NZS 4777.2, CEI 0-21, EN 50438, IEC 61683, IEC 61727, IEC 62116, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4					
Operating temperature	-25°C ~ +60°C (> 45°C downgrading)					
Relative humidity	0 ~ 100% (non-condensing)					
Altitude	2000 m					
Dimensions (W × D × H) (mm)	515 × 166.5 × 435					
Weight (kg)	25					

Disclaimer:

- These data in this document are tested under specified conditions. It may result in difference between actual results and these data due to some uncertain factors. The statement about this product is for reference only. It makes no representation or warranty.
- All specifications are subject to change without notice.