

Attestation of Conformity

No. N8A 076644 0019 Rev. 00

Holder of Attestation: EAST Group Co., Ltd.

No.6 Northern Industry Road

Songshan Lake Sci. & Tech. Industry Park 523808 DongGuan City, Guangdong Province

PEOPLE'S REPUBLIC OF CHINA

Product: Converter

(Hybrid Inverter)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290223084001

Date, 2023-07-03

(Billy Qiu)

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Attestation of Conformity

No. N8A 076644 0019 Rev. 00

Model(s): EAHI-6000-SL, EAHI-5000-SL, EAHI-3600-SL, EAHI-3000-SL

Parameters:

Model	EAHI-3000- SL	EAHI-3600- SL	EAHI-5000- SL	EAHI-6000- SL		
PV input rating						
Max. input power	4680W	4680W	6500W	7800W		
Rated input voltage	360Vd.c.					
Max. input voltage	550Vd.c.					
MPPT voltage range	100Vd.c. – 540Vd.c.					
MPPT voltage range (full load)	250Vd.c. – 450Vd.c.					
Max. input current	15Ad.c.		15Ad.c.*2			
PV short circuit current	20Ad.c.		20Ad.c.*2			
Battery input / output rating						
Battery type	Li-ion, Lead-acid battery					
Rated voltage	48Vd.c / 51.2Vd.c.					
Battery voltage range	42Vd.c. – 58Vd.c.					
Max. charging power	3000W	3600W	5000W	5000W		
Max. charging current	66Ad.c.	75Ad.c.	100Ad.c.	100Ad.c.		
Max. discharging power	3000W	3600W	5000W	6000W		
Max. discharging current	66Ad.c.	75Ad.c.	100Ad.c.	120Ad.c.		
Grid input rating						
Rated input voltage	230Va.c.					
Rated grid frequency	50Hz					
Max. input power	3000W	3600W	5000W	6000W		
Rated input current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.		
Max. input current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.		
Grid output rating						
Rated output power	3000W	3600W	5000W	6000W		
Max. output power	3000W	3600W	5000W	6000W		
Rated output voltage	230Va.c.					
Rated output frequency	50Hz					
Rated output current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.		

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Attestation of Conformity

No. N8A 076644 0019 Rev. 00

Max. output current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.			
Power factor	0.8 leading – 0.8 lagging						
AC load output rating							
Rated output power	3000W	3600W	5000W	6000W			
Max. output power	3000W	3600W	5000W	6000W			
Rated output voltage	230Va.c.						
Rated output frequency	50Hz						
Rated output current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.			
Max. output current	13.05 Aa.c.	15.7 Aa.c.	21.8 Aa.c.	26.09 Aa.c.			
General parameter							
Ingress protection rating	IP66						
Ambient temperature range	-25°C to 60°C (> 45°C derating)						
Protective class	Class I						

Tested according to:

EN 62109-1:2010 EN 62109-2:2011

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

