

Gaming UPS

1000VA ~ 2000VA




Features

- Pure sine wave output
- Microprocessor-based digital control
- Wide input voltage range
- Boost and buck AVR for voltage stabilization
- Auto sensing frequency
- Press the button to switch the RGB lighting
- Built in mute control button
- Built-in two USB charger ports for mobile devices
- Humanized alarm system
- Power-on self test
- Cold start
- Auto restart when mains power is restored
- Intelligent battery management
- Short circuit and overload protection
- Automatic charging in OFF mode
- USB & RJ45 communication port

Rear Panel

1. AC input
2. AC Breaker
3. Output Outlets
4. USB communication port(optional)



Optional outlets



Specifications

Model	1000VA	1500VA	2000VA
Rated power	600W	900W	1200W
Input			
Rated input voltage	100/110/120Vac or 220/230/240Vac		
Input voltage range	100/110/120Vac: 80~150Vac; 220/230/240Vac: 160~290Vac		
Frequency range	50Hz/60Hz(auto-sensing), 45~55Hz for 50Hz, 55~65Hz for 60Hz		
Output			
Output voltage(battery mode)	100/110/120Vac±10% or 220/230/240Vac±10%		
Output frequency(battery mode)	50Hz/60Hz±0.3Hz(auto-sensing)		
Waveform	pure sine wave		
Switching time	6ms(typical), 10ms(max.)		
Batteries			
DC voltage	24V		
Model & numbers	12V/7Ah×2	12V/9Ah×2	
Recharge time	6~8 h recharging to 90% capacity		
Charging current	1A(max.)		
Others			
Operating temperature	0~40°C		
Relative humidity	5~90%		
Dimensions(W×H×D)(mm)	99×280×420		
Packaged dimensions(W×H×D)(mm)	180×378×515		
Net weight(kg)	8.5	11.0	11.5
Gross weight(kg)	9.5	12.0	12.5

- All specifications are subject to change without notice
- Custom-made specifications are acceptable